

Quiz on Mar 14

Quiz on Mar 14

1.
If an organization has only 4096 hosts and is assigned a class B address, what is the address efficiency achieved by it? Express in percentage. Format X (e.g. 30)

Marks: 1

Type: FILL_IN_THE_BLANKS_TYPE

Answer: ["6,6.25"]

2. How many class A prefixes are there?

Marks: 1

Type: SINGLE_CORRECT_ANSWER

Options:

- 0) 128
- 1) 256
- 2) 16384
- 3) 65536

Answer: [0]

3.
An organization has a physical network with 4000 hosts, what type of addresses would you assign to maximize efficiency? Format X (e.g. A)

Marks: 1

Type: FILL_IN_THE_BLANKS_TYPE

Answer: ["B,b"]

4. Which of the following is TRUE about DHCP. Select all that apply.

Marks: 1

Type: MULTIPLE_CHOICE

Options:

- 0) Addresses handed out by server can be used until server asks for it back via a special message
- 1) DHCP operates at the network layer
- 2) DHCP Request messages sent by client are unicast
- 3) DHCP server passes default router information

Answer: [[3]]

5.

Address block is represented as A/X, where A is the address prefix and X is the prefix length. What is the maximum value of X? Format X (e.g. 8)

Marks: 1

Type: FILL_IN_THE_BLANKS_TYPE

Answer: ["32"]

6. Which of the following is true of subnetting? Select all that apply.

Marks: 1

Type: MULTIPLE_CHOICE

Options:

- 0) In subnetting, one class address is shared among many physical networks
- 1) In subnetting, multiple class addresses is shared among one physical network
- 2) All hosts on a given physical network have the same subnet number and mask
- 3) All routers outside organization have multiple entries against the organization for a given IP prefix.

Answer: [[0, 2]]

7.
DHCP offer (when the client is asking for an IP address for the very first time i.e. not renewing lease) is

Marks: 1

Type: SINGLE_CORRECT_ANSWER

Options:

- 0) Unicast
- 1) Multicast
- 2) Broadcast

Answer: [2]

8. Which of the following is true of ARP? Select all that apply.

Marks: 1

Type: MULTIPLE_CHOICE

Options:

- 0) Entries in the ARP cache are maintained indefinitely
- 1) Gratuitous ARP are only sent as ARP requests
- 2) ARP replies are broadcast
- 3) Gratuitous ARP help detect duplicate IP addresses

Answer: [[3]]

9. Which of the following is true of traceroute? Select all that apply.

Marks: 1

Type: MULTIPLE_CHOICE

Options:

- 0) Traceroute operates at the application layer
- 1) Relies on ICMP's "fragmentation required field" type/code
- 2) In traceroute sent messages, destination port is set to an unlikely number
- 3) Relies on "destination network unreachable" type/code

Answer: [[0, 2]]

10.

Which among the following ICMP message type/code does traceroute depend on

Marks: 1

Type: MULTIPLE_CHOICE

Options:

- 0) TTL expired
- 1) Port unreachable
- 2) Host unknown
- 3) Bad IP header

Answer: [[0, 1]]
